



cushion worx™

CushionWorx, a premium polyethylene foam cushion underlayment, performs with EcoWorx® carpet tile for comfort underfoot and sound reduction in high-traffic environments including hospitality, corporate offices, retail and healthcare applications. Users may not see CushionWorx, but they will experience a difference immediately.

- Delivers underfoot comfort with 3 mm thickness and reduces sound transfer when installed with EcoWorx carpet tile in commercial public spaces.
- Provides more noticeable underfoot comfort than with EcoWorx carpet tile alone.
- Adheres to concrete and wood subfloors with Shaw 3800 adhesive. Provide added stability by using Shaw 5100 adhesive to adhere EcoWorx carpet tile to CushionWorx.
- Impact Insulation Class (IIC) rating of 76 dB¹
- Sound Transmission Class (STC) rating of 66 dB¹
- Made in the USA

Specifications

| | |
|-------------------------------------|--------------------------|
| Style Number | 54829 |
| Description | Polyethylene |
| Roll Width | 76 inches |
| Roll Length | 150 linear feet |
| Thickness | 0.125 inch |
| Density | 4.0 lb/ft ³ |
| Roll Weight | 40 lbs |
| Square Yards Per Roll | 105.6 sq yds (950 sq ft) |
| Compression Set | 22% |
| Radiant Panel | Class 1 ² |
| Smoke Density Flaming / Non-flaming | <450 |

¹ Acoustical performance achieved when tested with EcoWorx carpet tile based on approved installation instructions.

² Radiant panel rating of Class 1 achieved when tested with EcoWorx carpet tile based on approved installation instructions.