

Shaw Industries, Inc. LokDots™ installation system for carpet tile is a pressure sensitive hot melt adhesive application system for the installation of polyolefin carpet tile. This dry adhesive method allows for ease of installation and installation in high moisture areas. It is designed for polyolefin tiles and should not be used for PVC, felt backed cushion tiles or tiles that contain plasticizers.

ITEM	COVERAGE	WEIGHT
SLEEVE (8 ROLLS)	250 yds*	3 lb**
SLEEVE (4 ROLLS)	125 yds*	2 lb**
CASE (96 ROLLS)	3,000 yds*	31 lb**
APPLICATOR	na	2 lb**

*minimum coverage - exception 9 x 36 tiles (8 rolls) 150 yds (4 rolls) 75 yds

** packaged weights

ENVIRONMENTAL

GREEN LABEL PLUS

Certified by Carpet & Rug Institute GLP 91802

CRADLE TO CRADLE

Silver Certified when used in conjunction with Philadelphia Commercial EcoWorx tile products

VOC

Virtually VOC free (<0.1 g/l)

WARRANTY

One year commercial limited warranty

INSTALLATION

MOISTURE LEVEL

Up to 10 lbs and 95% relative humidity

ALKALINITY

Up to 12 pH

APPROVED SUBFLOORS

Concrete, VCT, VAT, Primed Wood, Terrazzo, Raised Access Floors, Cutback, Pressure Sensitive and Multipurpose Adhesive, Advantech

- Assemble required material: LokDots Adhesive Rolls and Handheld Applicator.
- Level and clean floors.
- Apply dots according to the diagrams featured on the LokDots Installation Guidelines.
- Roll with a 75 lb roller.

For details on installation, refer to Philadelphia Commercial LokDots Installation Guidelines or www.lokdots.com.