

PRODUCT SPECIFICATIONS

STYLE NAME / NUMBER	Line Of Sight / 5543V
CONSTRUCTION	Advantium™ Core SPC
CLASS / ASTM F 1700	Class III Printed Film Vinyl Tile, Type B (embossed)
WEAR LAYER THICKNESS	20 mil or 0.020" (0.5 mm)
OVERALL THICKNESS	3 mm or 0.12"
PRODUCT SIZE	12" wide x 24" long (nominal)
FINISH	ExoGuard+™
INSTALLATION	Direct Glue
RECOMMENDED ADHESIVE	Shaw 4100 or S150

PACKAGING

SQUARE FEET PER CARTON	32 sf.
PIECES PER CARTON	16 pcs
WEIGHT PER CARTON	36.32 lbs
CARTONS PER PALLET	66 cartons
PALLETS PER TRUCKLOAD	18 pallets
CARTONS PER TRUCKLOAD	1,188 cartons

TESTING

SLIP RESISTANCE / ASTM D 2047	ADA Compliant
DIMENSIONAL STABILITY / ASTM F 2199	less than 0.020"/ft., Passes
STATIC LOAD / ASTM F 970 (MODIFIED)	2000 psi (lbs/sq. in.) - 0.005 in.
RESIDUAL INDENTATION / ASTM F 1914	Passes
RESISTANCE TO HEAT / ASTM F 1514	Passes
RESISTANCE TO LIGHT / ASTM F 1515	Passes
RESISTANCE TO CHEMICALS / ASTM F 925	Passes
RADIANT FLUX / ASTM 648	>0.45 watts/cm ² , NFPA Class I
SMOKE DENSITY / ASTM E 662	<450, Passes

WARRANTY

Lifetime Commercial Limited Warranty
10 Year Under Bed Warranty when installed with Shaw 4100 or S150 adhesive

ENVIRONMENTAL

INDOOR AIR QUALITY	FloorScore certified
LEED V4	Low emitting materials



Specifications are subject to nominal manufacturing variance.
Material supply and/or manufacturing processes may necessitate changes without notice.