

## PRODUCT SPECIFICATIONS

STYLE NAME / NUMBER	Revival / 5544V
CONSTRUCTION	Advantium™ Core SPC
CLASS / ASTM F 1700	Class III Printed Film Vinyl Tile, Type B (embossed)
WEAR LAYER THICKNESS	20 mil or 0.020" (0.5 mm)
OVERALL THICKNESS	3 mm or 0.12"
PRODUCT SIZE	18" wide x 36" long (nominal)
FINISH	ExoGuard+™
INSTALLATION	Direct Glue
RECOMMENDED ADHESIVE	Shaw 4100 or S150

## PACKAGING

SQUARE FEET PER CARTON	36 sf
PIECES PER CARTON	8 pcs
WEIGHT PER CARTON	40.75 lbs
CARTONS PER PALLET	50 cartons
PALLETS PER TRUCKLOAD	18 pallets
CARTONS PER TRUCKLOAD	900 cartons

## TESTING

SLIP RESISTANCE / ASTM D 2047	ADA Compliant
DIMENSIONAL STABILITY / ASTM F 2199	less than 0.020"/ft., Passes
STATIC LOAD / ASTM F 970 (MODIFIED)	2000 psi (lbs/sq. in.) - 0.005 in.
RESIDUAL INDENTATION / ASTM F 1914	Passes
RESISTANCE TO HEAT / ASTM F 1514	Passes
RESISTANCE TO LIGHT / ASTM F 1515	Passes
RESISTANCE TO CHEMICALS / ASTM F 925	Passes
RADIANT FLUX / ASTM 648	>0.45 watts/cm², NFPA Class I
SMOKE DENSITY / ASTM E 662	<450, Passes

## WARRANTY

Lifetime Commercial Limited Warranty  
10 Year Under Bed Warranty when installed with Shaw 4100 or S150 adhesive

## ENVIRONMENTAL

INDOOR AIR QUALITY	FloorScore certified
LEED V4	Low emitting materials



Specifications are subject to nominal manufacturing variance.  
Material supply and/or manufacturing processes may necessitate changes without notice.